

FonTel ISDN2NET

PHONE CALL RECORDER

- ✓ Records calls performed on 2 ISDN lines
- ✓ Build-in HDD
- ✓ Accessible via LAN
- ✓ Works without PC



FonTel ISDN2NET phone call recorder is an independent device designed to record the contents of the phone calls performed on 2 ISDN BRI phone lines (2B+D). Calls and database with other information are recorded at build in HDD. Listening of the calls is possible via LAN with internet browser or using included software.

Device features

- independent call recording on 2 ISDN BRI phone lines (4 voice channels)
- build-in HDD for many thousand hours of recording
- perfect sound quality
- unplug cable alert (recording supervision)
- records incoming only, outgoing only or all calls in any direction
- measurement of the operator's ring tone reaction time (delay in getting the phone)
- identification of incoming, outgoing and unanswered calls
- new (not listened) calls marking
- identification of the caller number (CLIP)
- identification of the MSN / DDI numbers
- automatic control of available hard disk space (automatic removal of the oldest recordings)
- built-in real time clock with battery
- support NTP time servers for time synchronization
- access to the device via LAN/Internet
- configuration, operation, call browsing, searching and listening via internet browser
- access to the device protected with a password from unauthorized use
- cooperation with other systems by providing API for developers
- support **FonTel Client** software

Software **FonTel Client** features

- call playback independent of the recording
- a note can be introduced to any call
- an user label can be attached to any call
- printing the list of calls
- export of the list of calls to CSV format
- easy generation of archive copies (also directly on a CD/DVD)
- call graphical representation
- phone book embedded that allows to define individual numbers, as well as number pools
- caller's number provided even before the phone is answered
- searching the recorded calls by line's number, date, call's number, note, time period
- statistics and charts of reordered calls
- list of pending calls

Technical specification

- line connection: 2 x RJ45 socket (S0 interface)
- LAN connection: RJ45 socket
- supervision interface: Jack Mono 3,5mm
- power supply: 230V 50Hz (100-240V, 50/60Hz)
- dimensions: 44 x 316 x 165 mm (h x w x d)

Contents of the package

- FonTel ISDN2NET** phone call recorder
- power supply cable
- 2m LAN cable (2 x RJ45)
- user's manual
- CD with **FonTel Client** software